




8060



Biloba
oil dynamic hinge



- Cerniera oleodinamica con regolazione delle velocità di chiusura dell'anta per porte in battuta. Ideale per chiusure ermetiche. Stop a 0° +90°.
- Bisagra cierra puerta hidráulica con ajuste de velocidad de cierre de la puerta con tope. Lo perfecto por cerradura hermética. Freno a 0°, +90°.
- Hydraulic hinge with adjustment of the closing speed of the door with stop. Ideal for hermetic closing. Stop at 0° +90°.
- Automatik- Hydraulikscharnier mit Regulierung der Schließgeschwindigkeit der Tür. Für Anschlagtüren geeignet. Ideal für hermetische Schließung. Feststellung bei 0°+90°.
- Charnière hydraulique avec réglage de la vitesse de fermeture du battant pour porte avec butée. Idéal pour fermetures hermétiques. Stop à 0 +90°.



Classificazione secondo normativa - Clasificación según la ley - Classification according to int'l regulation Klassifizierung nach den Vorschriften - Classification selon la norme									
art. 8060	UNI EN 1154 : 2006	3	8	2	5	0	1	4	



- * Distanza minima da filo muro per consentire rotazione vetro
Distancia mínima de hilo pared, para facilitar la rotación del vidrio
Minimum distance from wall edge in order to facilitate glass rotation
Mindestdistanz von der Wandkante, um die Glasrotation zu erleichtern
Distance minimum de l'arrête du mur pour permettre la rotation du verre

TESTATA 1.000.000 CICLI
TESTED FOR 1.000.000 CYCLES